

External WiFi antenna to Radio module via Coax cable



**J3.KIT - Wi-Fi radio module**  
Static IP: 172.21.161.1

Access here with browser to choose Wi-Fi Hotspots.  
Usr: ubnt  
Pwd: ubnt

**J3.KIT - Router 950**  
4G dual SIM / Wi-Fi hotspot  
Static IP: 192.168.77.1

Access here with browser to:  
- manage SIMs.  
- change wi.fi password for Guests.  
Usr: admin  
Pwd: \_\_\_\_\_

Wi-fi ID for guests:  
WIBOAT.MAITAI.GUEST  
Pwd: \_\_\_\_\_



for GUESTS (hotspots and 4G only):  
WIBOAT.MAITAI.GUEST




for CREW (hotspots, 4G and SAT):  
WIBOAT.MAITAI



**J5.KIT - Router mod. 2011**  
Static IP: 192.168.88.1 (Gateway)  
- Eth1 : ONLY for router 950  
- Eth3 : navigation PC (Dhcp)  
- Eth5 : ONLY for Inmarsat FBB  
- Eth4-6-7-8-9-10: free use (Dhcp)  
Dhcp range: 192.168.100-254

Access here with browser to:  
- enable / disable 950 to use SAT FBB.  
- change wi.fi password for crew.  
Usr: setup  
Pwd: \_\_\_\_\_

Wi-fi ID for crew:  
WIBOAT.MAITAI  
Pwd: \_\_\_\_\_



Connect radio module ONLY to WAN port of RUT950

Connect LAN1 port ONLY to ETH1 port of RB2011

Connect LAN1 port ONLY to ETH5 port of RB2011

**Inmarsat FBB phone**  
Static IP: 172.21.165.1

Access here with browser to check and manage sat account.  
Usr:  
Pwd:



Yacht: MAITA'I	Wi.Boat system connection Vers. J3-J5 Routers 950 - 2011
Cliente: Sailaway ltd	Notes:
Data: Ottobre 2015 - Napoli	Nautigamma Trade srl www.nextboat.it